

ArcticChill 88CL

Exceptional Capacity Plus Contactless Dispensing
To Avoid Hand To Tap Contamination

- Direct chill cold water cooler
- Single dispensing button for chilled water
- Can be fitted with overflow kits & mains drainage
- Fits our standard cowl and wall bracket
- WRAS approved
- FloodGuard inlet solenoid protects the cooler against large scale flooding
- Impressive 23cm dispensing height
- Fitted with contactless dispensing

Contactless Dispensing

- An infra red sensor activates dispensing when you place your hand approximately 4cm in front of the sensor
- Hi-visibility clothing may activate dispensing when in proximity <1m



23cm Dispensing
Height To Fill
Bottles

Delivers 30 - 40 Litres
Per Hour Of Chilled
Water Below 12 °C

AA FIRST
WATER COOLERS
& BOILERS



Quality – Reliability – Integrity

ArcticChill 88CL

Exceptional Capacity Plus Contactless Dispensing
To Avoid Hand To Tap Contamination



ArcticChill 88CL Infra Red Sensor Enables Contactless Dispensing

- Green power LED indicates power is on
- Orange LED will light up during dispensing
- To activate dispensing place your hand in front of the sensor <4cm
- Hi-visibility clothing may activate dispensing when in proximity <1m

Accessories For The ArcticChill 88

Installation rail with filter. Includes compression fitting, 1-Micron green filter, water block, copper pressure reducing valve & non-return valve



FloodGuard - closed inlet solenoid only opens to allow water into the cooler, when water is dispensed. By remaining closed all other times it protects the cooler against leaks



Filter housing with carbon block candle & nanofilter



Mains drainage - connect the drip tray to mains drainage. Can be supplied with a pump, to pump the water over 50m & a rise of 5m



Cowling to fix the cooler securely to the wall. (Supplied separately)



10 litre overflow system with alarm to signal when full. (Factory fitted)



3 Litre overflow kit connects the drip tray to a 3 litre alarmed overflow container. The container has a tap to empty without removing it



A pumped main drainage system pumps the waste water from the drip tray over a distance of 100m & a rise of 5m. (Factory installed)



Description	Dimensions H X W X D (MM)	Weight (Kg)
POU Floor Standing	1135 x 340 x 340	25
POU Table Top	460 X 340 X 340	175